


STEP**19**

Be careful to assemble all components in the sequence they are presented.

NOTE:

All pulleys are the 4 1/4" diameter Pulleys (26), except where noted.

Low Pulley Cable (35)

- A. Insert metal ball end of Low Pulley Cable (35) at Low Pulley Frame (AY). Insert metal ball end of Cable (35) under Pulley (E1).
- B. Route Cable (35) over Pulley (E2), and attach Pulley (E2) to the bottom of Pulley Plates (132) using:
 - One 76 (3/8"x 1 3/4" hex head bolt)**
 - Two 94 (3/8" washer)**
 - One 91 (3/8" nylon lock nut)**
- C. Route Cable (35) under Pulley (E3).
- D. Route Cable (35) over Pulleys (E4) and (E5).
- E. Route Cable (35) through Pulley Holder With Hook (133) as shown. Install Pulley (E6) using:
 - One 76 (3/8"x 1 3/4" hex head bolt)**
 - Two 94 (3/8" washer)**
 - One 91 (3/8" nylon lock nut)**
- F. Remove Pulley (E7) from pulley housing. Insert Cable (35) into pulley housing as shown and reinstall Pulley (E7).*

***Note:**

Leave the bolt going through Pulley (E7) hand tight until the end of Cable Adjustments in Step 21.

- G. Remove Bolt (56) from Selector Rod Top Bolt (52), slide Cable (35) through Selector Rod Top Bolt (52). Attach Cable End Shaft (135) and tighten Allen Screw (136). Pull Cable (36) tight, so Cable End Shaft (135) fits inside Selector Rod Top Bolt (52). Reinstall Bolt (56) in Selector Rod Top Bolt (52).

